



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04N 7/173	A1	(11) International Publication Number: WO 97/31483
		(43) International Publication Date: 28 August 1997 (28.08.97)

(21) International Application Number: PCT/US97/02707


(22) International Filing Date: 21 February 1997 (21.02.97)

(30) Priority Data:  
08/605,908 23 February 1996 (23.02.96) US(71) Applicant: DSC COMMUNICATIONS CORPORATION  
[US/US]; 1000 Coit Road, Plano, TX 75075 (US).(72) Inventor: EHRETH, David; 1540 Laguna Road, Santa Rosa,  
CA 95401 (US).(74) Agent: FISH, Charles, S.; Baker & Eotts, L.L.P., 2001 Ross  
Avenue, Dallas, TX 75201-2980 (US).(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,  
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE,  
HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS,  
LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL,  
PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA,  
UG, UZ, VN, YU, ARIPO patent (KE, LS, MW, SD, SZ,  
UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,  
TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF,  
BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: METHOD AND SYSTEM FOR COMMUNICATING VIDEO SIGNALS TO A PLURALITY OF TELEVISION SETS



## (57) Abstract

A video communications system (10) includes a communications controller (30) that interfaces with a broadband/narrowband network (40) to distribute video signals to a plurality of remote sites (104) in a multi-site location (102). Each remote site (104) includes a channel selector and signalling unit (50) and at least one television set (100). A user enters user input information into a remote selector (70) for processing by the channel selector and signalling unit (50). The channel selector and signal unit (50) sends the user input information to the communication controller (30) over a video signal distribution network (90) at an upstream frequency selected at a user selectable setting (52). The communication controller (30) responds by modulating the desired video information onto a downstream frequency for transmission to the television set (100) on the video signal distribution network (90). Each remote site (104) has a separate upstream frequency and downstream frequency to allow for independent control of each television set (100).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

METHOD AND SYSTEM FOR COMMUNICATING  
VIDEO SIGNALS TO A PLURALITY OF TELEVISION SETS

TECHNICAL FIELD OF THE INVENTION

5 This invention relates generally to communications systems and more particularly to a method and system for communicating video signals to a plurality of television sets on a single video signal distribution network.

BACKGROUND OF THE INVENTION

10 Many people have multiple television sets or other information transceivers in their homes. When multiple television sets receive information signals from a single video signal distribution network, a separate set top controller must be connected to each television set in  
15 order to allow different information signals to be received by each television set.

One method used to allow multiple television sets to be independently controlled from remote sites involves a subscription cable television system and a number of  
20 subscriber drops. Such a method, however, does not allow users to independently control multiple television sets serviced by the same subscriber drop without the use of multiple set top controllers. The television sets in these systems must therefore be "chained" together on the same  
25 subscriber drop, each television set having its own set top controller. The use of multiple set top controllers,

especially in a home environment, adds undesirable complexity and cost to the cable network. Therefore, it is desirable to have independent control and operation for each of a plurality of television sets on a single video signal distribution network using at most one set top box.

#### SUMMARY OF THE INVENTION

In accordance with the teachings of the present invention, a method and system for communicating video signals to a plurality of television sets are provided which substantially eliminate or reduce disadvantages and problems associated with prior methods and systems for transmitting selected information to each of a plurality of television sets.

According to an embodiment of the present invention, there is provided a multiple site video distribution system that includes a communication controller that receives video information from a telecommunications network. The communication controller transmits selected video signals from the video information onto a video signal distribution network. A first channel selector and signaling unit sends user input information to the communication controller over the video signal distribution network at a first upstream frequency. The user input information includes a request to receive a first video signal. The communication controller selects the first video signal from the video information in response to the user input information from the first channel selector and signaling unit. The communication controller modulates the first video signal onto a first downstream frequency for transmission to the first channel selector and signaling unit over the video signal distribution network.

A second channel selector and signaling unit sends user input information to the communication controller over

the video signal distribution network at a second upstream frequency. The user input information includes a request to receive a second video signal. The communication controller selects the second video signal from the video information in response to the user input information from the second channel selector and signaling unit. The communication controller modulates the second video signal onto a second downstream frequency for transmission to the second channel selector and signaling unit over the video signal distribution network.

The present invention provides various technical advantages over conventional cable television subscription services. For example, one technical advantage is to independently control a plurality of television sets that receive video signals from a single video signal distribution network. Another technical advantage is to eliminate the need to "chain" together multiple set top controllers, thereby reducing cost and complexity for both the user and the network operator. Yet another technical advantage is to reduce the uncertainty relating to the electrical or optical characteristics of the drop termination. Still another technical advantage is to reduce the required complexity of upstream multiple access protocols, which may reduce the cost and complexity that would be associated with set top controllers used in prior systems.

Another important technical advantage of the present invention is the fact that it increases the effectiveness and efficiency of network drop technologies that have distance limitations. Using the present invention, for example, the entire length of a copper drop transceiver with a maximum loop length of five hundred feet would be available for use between the network element (e.g., ONU) and the communications controller. A portion of the five

hundred feet would therefore not need to be allocated to connect numerous "chained" set top controllers within a home or other multiple-site structure. Eliminating such "chaining" configurations may make, for example, up to two hundred feet of transmission distance available, resulting in substantial cost savings to the network.

A further technical advantage is to avoid placing all the video signals onto the single video signal distribution network for selective pick off by the tuner of the television set through the set top controller as is done in conventional cable television systems. Only those video signals currently desired are placed on the single video signal distribution network by selective modulation onto separate frequency carriers for each of the television sets on the network. Other technical advantages are readily apparent to one skilled in the art from the following figures, descriptions, and claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present invention and its advantages, reference is now made to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features and wherein:

FIGURE 1 is a schematic representation of a video communications system servicing multiple television sets on a single video signal distribution network.

#### DETAILED DESCRIPTION OF THE INVENTION

FIGURE 1 is a schematic representation of a video communications system 10. Video communications system 10 includes a communications controller 30 placed in a convenient location associated with a multi-site location

102, such as a home or business, having a plurality of television sets 100. Communications controller 30 provides data and video signals to the plurality of television sets 100 within multi-site location 102. Multi-site location 102 includes a plurality of remote sites 104, each having a channel selector and signalling unit 50 and at least one corresponding television set 100. Though shown as a separate unit, channel selector and signaling unit 50 may be incorporated within or integrated into television set 100. Remote sites 104 may represent different units in a multiple-site structure, for example, an apartment complex, hotel, or other large building. Remote sites 104 may also represent separate parts of a residential dwelling, office, or other structure. For illustration purposes, remote sites 104 are discussed herein as located within a typical residential dwelling.

Communications controller 30 is coupled to a broadband/narrowband network 40 through a drop cable 20. Broadband/narrowband network 40 provides the data and video signals for distribution to television sets 100 through communications controller 30. Broadband/narrowband network 40 may provide all data and video signals subscribed to by multi-site location 102 or only those signals requested by communication controller 30. Drop cable 20 is operable to transmit data and video signals from broadband/narrowband network 40 to communications controller 30. Drop cable 20 may be a twisted conductor pair, conventional coaxial cable, fiber optic transmission line, or other suitable signal transmission medium. Communications controller 30 includes a network interface 32 that communicates with broadband/narrowband network 40 for termination of video information coming in from broadband/narrowband network 40 over drop cable 20. Network interface 30 is also operable to conduct ATM cell management and generation activities,

including multiple ATM sessions. Network interface 32 may further convert ATM cells carrying Motion Picture Experts Group (MPEG) encoded video to an analog format. Though shown to be located within multi-site location 102, communications controller 30 may be incorporated within or integrated into broadband/narrowband network 40.

Communications controller 30 includes an upstream signaling receiver 80. In connection with upstream signaling receiver 80, communications controller 30 is operable to receive and manage upstream information signals from channel selector and signalling unit 50 at each remote site 104. Communications controller 30 also includes a modulating unit 34 that is operable to select and modulate video information from network interface 30 into downstream information signals for transmission onto any one of a plurality of downstream RF channels for appropriate distribution to television sets 100 through respective channel selector and signaling units 50. Downstream information signals include data and video signals, and may be in analog form, digital form, a combination of analog and digital, or may have other signal forms suitable for data and video information transmission.

Television sets 100, through corresponding channel selector and signaling units 50, are coupled to a video signal distribution network 90 of the type currently used for subscription cable television. Video signal distribution network 90 is operable to transmit information signals to, from, and between upstream signaling receiver 80, channel selector and signalling unit 50, and television sets 100. The present invention also contemplates other transmission media operable to combine with or replace the functions of video signal distribution network 90. Although television sets are discussed herein, the present invention contemplates other transceivers, including



computer monitors, operable to receive incoming information signals and communicate the received information to a user or users.

5 In one embodiment, the user enters user input information into channel selector and signaling unit 50 through a remote selector 70. User input information are transmitted on video signal distribution network 90 as upstream information signals and may include a video channel selection, viewer response or opinion data, program rating information, or other information to be communicated  
10 upstream from a user or users at a remote site 104. Remote selector 70 may be similar to devices currently used to remotely control televisions or other electronic devices using infrared radiation. Although remote selector 70 is discussed herein as transmitting information entered by the user using infrared radiation, the present invention  
15 contemplates other suitable signal transmission media for entering user input information.

Channel selector and signalling unit 50 is coupled to  
20 video signal distribution network 90 such that channel selector and signalling unit 50 is operable to receive signals from and transmit signals to other components of the system over video signal distribution network 90. Channel selector and signalling unit 50 is operable to  
25 receive user input information entered by a user from remote selector 70, and to transmit the user input information as upstream information signals to upstream signaling receiver 80 associated with communications controller 30 over video signal distribution network 90.

30 Channel selector and signalling unit 50 includes a user selectable setting 52. The user selects an upstream frequency setting at user selectable setting 52, which corresponds to a pre-determined upstream frequency at which channel selector and signalling unit 50 is to transmit

upstream information signals to upstream signaling receiver 80 over video signal distribution network 90. The upstream frequency setting at user selectable setting 52 is different from the upstream frequency setting at any other user selectable setting 52 of other channel selection and signaling units 50 on video signal distribution network 90. The selected upstream frequency setting is communicated to upstream signaling receiver 80 over video signal distribution network 90. The upstream information signals transmitted by channel selector and signalling unit 50 to upstream signaling receiver 80 communicate the user input information entered by the user from remote selector 70. For illustration purposes, user input information is discussed as including the selection of a channel from which the user wishes to receive video information.

Channel selector and signalling unit 50 transmits upstream information signals containing the desired channel selection to upstream signaling receiver 80 at the upstream frequency determined by user selectable setting 52. Upstream signaling receiver 80 may be located within communications controller 30 or at any other suitable location that allows communications controller 30 to function in coordination with upstream signaling receiver 80. Upstream signaling receiver 80 is operable to receive upstream information signals from channel selector and signalling unit 50 over video signal distribution network 90 and, in response thereto, to transmit downstream information signals containing the selected video information to the appropriate television set 100 through the selecting channel selector and signaling unit 50 over video signal distribution network 90. Upstream signaling receiver 80 transmits downstream information signals at a downstream frequency that is pre-determined according to and associated with the selected upstream frequency.

In response to receiving upstream information signals from the plurality of channel selector and signalling units 50 within video communications system 10 over different upstream frequencies, upstream signaling receiver 80 is operable to transmit downstream information signals to television sets 100 associated with the plurality of remote sites 104. Each channel selector and signaling unit 50 is set to its own downstream frequency according to its corresponding upstream frequency selected at user selectable setting 52. Since the downstream frequency of each channel selector and signaling unit 50 is different and determined according to the corresponding upstream frequency, communications controller 30 may transmit video information to one or more television sets 100 at each remote site 104 independently of the other television sets 100 at other remote sites 104. Upstream signaling receiver 80 modulates downstream information signals onto appropriate downstream frequencies for transmission to appropriate channel selector and signaling units 50.

By way of example, a user at remote site 104 may be instructed that if the upstream frequency setting on user selectable setting 52 is selected to "5", the user will receive all video information on channel 5 corresponding to the downstream frequency and associated with the upstream frequency setting. The user need only select the video information desired using remote selector 70 and have television set 100 tuned to channel 5 for appropriate viewing. Further, a second user having an upstream frequency setting of "6" may receive video information on corresponding television set 100 tuned to channel 6 according to its corresponding downstream frequency. { Each remote site 104 has an upstream frequency on which to transfer user input information and a separate downstream frequency on which to receive video signals. }

In summary, a video communications system has an upstream frequency for transmitting user input information from a channel selector and signalling unit 5 to an upstream signaling receiver over a video signal distribution network. In response to the upstream frequency, an upstream signaling receiver selects an appropriate downstream frequency upon which is modulated downstream information signals that include desired video information. Because of the broad range of frequencies available, numerous television sets at remote sites may be accommodated by a single communications controller. One or more television sets at each remote site are therefore independently controlled using a single drop cable.

Thus, it is apparent that there has been provided, in accordance with the present invention, a method and system for independently communicating video information to a plurality of television sets that satisfy the advantages set forth above. Although the present invention has been described in detail, it should be understood that various changes, substitutions, alterations, and modifications can be made herein without departing from the spirit and scope of the invention as defined by the appended claims.

WHAT IS CLAIMED IS:

1. A communication controller for providing video information to a plurality of television monitors, comprising:

5 a network interface operable to receive video information from a telecommunications network;

an upstream signalling receiver operable to receive user input information associated with each of a first one and a second one of the plurality of television monitors, the user input information associated with the first one of the plurality of television monitors including a request for a first video signal, the user information associated with the second one of the plurality of television monitors including a request for a second video signal, the upstream signalling receiver receiving user input information associated with the first one of the plurality of television monitors on a first upstream frequency, the upstream signalling receiver receiving user input information associated with the second one of the plurality of television monitors on a second upstream frequency;

20 a modulating unit operable to select the first and second video signals from the video information received by the network interface in response to the user input information received by the upstream signalling receiver, the modulating unit operable to transmit the first video signal to the first one of the plurality of television monitors on a first downstream frequency, the modulating unit operable to transmit the second video signal to the second one of the plurality of television monitors on a second downstream frequency.

2. The communication controller of Claim 1, wherein the first video signal is the same as the second video signal.

3. The communication controller of Claim 1, wherein  
the first downstream frequency corresponds to a frequency  
tuned to by the first one of the television monitors and  
5 the second downstream frequency corresponds to a frequency  
tuned to by the second one of the plurality of television  
monitors.

4. The communication controller of Claim 1, wherein  
10 the network interface sends a request to receive the first  
video signal to the telecommunications network in response  
to the first video signal not being present in the video  
information.

5. The communication controller of Claim 1, wherein  
15 the network interface is operable to convert video  
information carried by asynchronous transfer mode cells  
into an analog format.

6. The communication controller of Claim 1, wherein  
20 the modulating unit determines a value of the first and  
second downstream frequencies in response to a value of the  
first and second upstream frequencies.

7. A method of communicating video signals to a plurality of television sets, comprising the steps of:

receiving video information from a telecommunications network;

5 receiving a request for a first video signal over a first upstream frequency;

receiving a request for a second video signal over a second upstream frequency;

10 selecting the first video signal and the second video signal from the video information;

modulating the first video signal onto a first downstream frequency;

modulating the second video signal onto a second downstream frequency;

15 transmitting the first video signal at the first downstream frequency;

transmitting the second video signal at the second downstream frequency.

20 8. The method of Claim 7, further comprising the steps of:

associating the first upstream frequency with the first downstream frequency;

25 associating the second upstream frequency with the second downstream frequency.

9. The method of Claim 7, further comprising the step of:

30 requesting the first video signal from the telecommunications network in response to the first video signal not being present within the video information.

10. The method of Claim 7, wherein the first video signal is the same as the second video signal.

14

11. The method of Claim 7, further comprising the step of:

adjusting a value of the first and second upstream frequencies.

5

12. The method of Claim 7, further comprising the step of:

determining a value of the first and second downstream frequencies in response to a value of the first and second upstream frequencies.

10



13. A multiple site video distribution system, comprising:

5 a communications controller operable to receive video information from a telecommunications network, the communication controller operable to transmit selected video signals from the video information over a video signal distribution network;

10 a first channel selector and signaling unit associated with a first television set and operable to send user input information over a first upstream frequency of the video signal distribution network to the communications controller, the user information including a request to receive a first video signal, the communications controller operable to select the first video signal from the video information and modulate the first video signal onto a first downstream frequency, the communications controller operable to send the first video signal to the first channel selector and signaling unit and the first television set over the video signal distribution network at the first downstream frequency;

20 a second channel selector and signaling unit associated with a second television set and operable to send user input information over a second upstream frequency of the video signal distribution network to the communications controller, the user information including a request to receive a second video signal, the communications controller operable to select the second video signal from the video information and modulate the second video signal onto a second downstream frequency, the communications controller operable to send the second video signal to the second channel selector and signaling unit and the second television set over the video signal distribution network at the second downstream frequency.

14. The video distribution system of Claim 13, wherein the first and second channel selector and signaling units have a user selectable setting to adjust a value of the first and second upstream frequencies respectively.

5

15. The video distribution system of Claim 13, wherein user input information is received by the first and second channel selector and signaling units by infrared remote transmission means.

10


16. The video distribution system of Claim 13, wherein the communication controller determines a value of the first and second downstream frequencies according to a value of the first and second upstream frequencies respectively.

15

17. The video distribution system of Claim 11, wherein the communication controller sends a request to receive the first video signal to the telecommunications network in response to the first video signal not being present in the video information.

20

1/1



# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 97/02707

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 6 H04N7/173		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 6 H04N		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A  A	WO 95 30305 A (AT & T CORP) 9 November 1995 see the whole document  --- ISS '95. WORLD TELECOMMUNICATIONS CONGRESS. (INTERNATIONAL SWITCHING SYMPOSIUM). ADVANCED SWITCHING TECHNOLOGIES FOR UNIVERSAL TELECOMMUNICATIONS AT THE BEGINNING OF THE 21ST. CENTURY BERLIN, APR. 23 - 28, 1995, vol. 2, 23 April 1995, VERBAND DEUTSCHER ELEKTROTECHNIKER (VDE) ET AL, pages 271-275, XP000495666 KAFKA H J ET AL: "INTERACTIVE VIDEO AND MULTIMEDIA SERVERS IN PUBLIC NETWORKS" see page 273, paragraph 3.2 --- <div style="text-align: center;">-/-</div>	1,7,13  2-6, 8-12, 14-17  1-17
<div style="display: flex; justify-content: space-between;"> <span><input checked="" type="checkbox"/> Further documents are listed in the continuation of box C.</span> <span><input checked="" type="checkbox"/> Patent family members are listed in annex.</span> </div>		
<b>* Special categories of cited documents:</b> <div style="display: flex;"> <div style="flex: 1;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="flex: 1;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"A" document member of the same patent family</p> </div> </div>		
Date of the actual completion of the international search	Date of mailing of the international search report	
13 May 1997	10.06.97	
Name and mailing address of the ISA European Patent Office, P.B. 3818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-3340, Tr. 31 631 epo nl, Fax (+ 31-70) 340-3016		Authorized officer  Greve, M

# INTERNATIONAL SEARCH REPORT

Int. .tional Application No

PCT/US 97/02707

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 481 757 A (MIHARA YOSHIKAZU ET AL) 2 January 1996 see column 2, line 5 - column 5, line 1 ---	1-17
A	US 5 459 506 A (BUSHNELL WILLIAM J) 17 October 1995 see abstract ---	1-17
A	EP 0 094 794 A (COMMUNICATIONS PATENTS LTD) 23 November 1983 see abstract -----	1,7,13

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/02707

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9530305 A	09-11-95	AU 8016394 A EP 0757875 A	29-11-95 12-02-97
US 5481757 A	02-01-96	JP 6141319 A JP 6153193 A JP 6153197 A JP 6153196 A	20-05-94 31-05-94 31-05-94 31-05-94
US 5459506 A	17-10-95	NONE	
EP 0094794 A	23-11-83	AU 1455583 A CA 1230668 A DE 3382546 A EP 0401873 A GB 2121656 A,B GB 2164229 A,B JP 59040787 A US 4538174 A	17-11-83 22-12-87 27-05-92 12-12-90 21-12-83 12-03-86 06-03-84 27-08-85